



Artico S

Description

Here is the new Saeco Artico line. This successful line of snack & food machines has a completely new design and modern graphics. Artico S is the new generation of 6-spirals snack & food vending machines with 6 removable trays for dispensing snacks, cold beverages in cans or bottles and, in the food configuration (from 0° to 4°C), also sandwiches and fresh products. It matches perfectly with the freestanding hot Cristallo Evo 400 vending machine, with which can share the payment system.

Accessories

- RSI programming key
- Eva-Dts kit
- Wall mounting brackets kit
- Pedestal kit

Main features

- Programmable temperature (snack or food)
- Optimized ventilation to reduce energy consumption
- Possibility to create menus for selling more combined products
- New 16-bit electronics
- Possibility to install 3 payment systems at the same time
- Accepts the most commonly used parallel and standard MDB, BDV and Executive payment systems

User interface

- Backlit capacitive keyboard with 12 buttons
- 128x64 pix graphic display
- Antivandalic coin introduction as standard

Technical data

Artico S

Structural specifications

Dimensions (w x h x d)	713 x 1700 x 870 mm
Overall size with open door	1358 mm
Weight	200 kg

Electrical specifications

Power supply	230 V/50 Hz
Power consumption	420 W
Consumption	1594 kw/h

Other specifications


Number of trays	6
Bottle tray	36 bottles
Can tray	36 cans
Snack tray	according to the spiral type
Number of spirals	36
Available spirals	24 (19 products) to 80 (6 products)
Adjustable temperature	
Food configuration	
snack	8°C - 16°C
food/Tetra Pak	0°C - 4°C

Technical specifications

- Programmable temperature based on product assortment
- The removable slot allows servicing the machine without interacting with the refrigerated area. The slot supports CPU, payment systems, display, keypad and closes the cash box area.
- Steel-sheet structure
- Photocells
- Wide product dispensing compartment, with opening to the outside
- Height of the cells containing the trays equal to 1136 mm
- Removable plastic trays, which provide a suitable resistance to weight. The tray position can be easily adjusted with 10 mm shifts.
- Self configuration with automatic reset at every machine start
- LED lighting
- Programming of sale prices
- Programmable RS1 Riolda lock
- CE, IMQ approved



Configuration



Artico S
+
Cristallo Evo 400