



Artico S

Description

Here is the new Saeco Artico line. This successful line of snack & food machines has a completely new design and modern graphics. Artico S is the new generation of 6-spirals snack & food vending machines with 6 removable trays for dispensing snacks, cold beverages in cans or bottles and, in the food configuration (from 0° to 4°C), also sandwiches and fresh products. It matches perfectly with the freestanding hot Oasi 400 vending machine, with which can share the payment system.

Accessories

- RSI programming key
- Eva-Dts kit
- Wall mounting brackets kit
- Pedestal kit

Main features

- Programmable temperature (snack or food)
- Optimized ventilation to reduce energy consumption
- Possibility to create menus for selling more combined products
- New 16-bit electronics
- Possibility to install 3 payment systems at the same time
- Accepts the most commonly used parallel and standard MDB, BDV and Executive payment systems
- New cooling unit with R290 technology with low environmental impact and high energy saving

User interface

- Backlit capacitive keyboard with 12 buttons
- 128x64 pix graphic display
- Antivandalic coin introduction as standard

Technical data

Artico S

Structural specifications

| | |
|-----------------------------|---------------------|
| Dimensions (w x h x d) | 713 x 1700 x 870 mm |
| Overall size with open door | 1358 mm |
| Weight | 200 kg |

Electrical specifications

| | |
|-------------------|-------------|
| Power supply | 230 V/50 Hz |
| Power consumption | 420 W |
| Consumption | 1594 kw/h |

Other specifications

| | |
|------------------------|-------------------------------------|
| Number of trays | 6 |
| Bottle tray | 36 bottles |
| Can tray | 36 cans |
| Snack tray | according to the spiral type |
| Number of spirals | 36 |
| Available spirals | 24 (19 products) to 80 (6 products) |
| Adjustable temperature | |
| Food configuration | |
| snack | 8°C - 16°C |
| food/Tetra Pak | 0°C - 4°C |
| Energy class (R290) | D |

Technical specifications

- Programmable temperature based on product assortment
- The removable slot allows servicing the machine without interacting with the refrigerated area. The slot supports CPU, payment systems, display, keypad and closes the cash box area.
- Steel-sheet structure
- Photocells
- Wide product dispensing compartment, with opening to the outside
- Height of the cells containing the trays equal to 1136 mm
- Removable plastic trays, which provide a suitable resistance to weight. The tray position can be easily adjusted with 10 mm shifts.
- Self configuration with automatic reset at every machine start
- LED lighting
- Programming of sale prices
- Programmable RS1 Rielda lock
- CE, IMQ approved



Configuration

| | | | | | |
|--------|--------|---------|---------|--------|--------|
| 8 prod | | 8 prod | | 8 prod | |
| 8 prod | 8 prod | 11 prod | 15 prod | 8 prod | 8 prod |
| 8 prod | 8 prod | 11 prod | 15 prod | 8 prod | 8 prod |
| 6 prod | 6 prod | 6 prod | 6 prod | 6 prod | 6 prod |
| 6 prod | 6 prod | 6 prod | 6 prod | 6 prod | 6 prod |
| 6 prod | 6 prod | 6 prod | 6 prod | 6 prod | 6 prod |



Artico S
+
Oasi 400